

N O R D F Ä R G

GRUND

Nordfärg Grund is a waterborne primer, especially created for painting all interior woodwork including doors, skirting boards, architraves and shelves. It can also be used on furniture. Grund has a high level of adhesion to most surfaces. Grund is easy to apply, flows well and has excellent colour opacity because of the high solid content.

AREA OF USE

Interior: Wooden surfaces.

Substrates: Doors, skirting boards, architraves, shelves etc.

APPLICATION

Previously painted surfaces should be sanded first. Thereafter, the surface must be stable, dry and free of dust, sand, loose old paint, dirt, grease or oil. On rough surfaces, it may be necessary to dilute the paint by about 10% with fresh water. Apply under controlled conditions, where air, paint and surface temperature are not below 5°C (preferably 10°C or more), with relative humidity below 85%. Surface temperature should be between 5°C and 35°C.

TECHNICAL INFORMATION

Coverage: 6-8m²/litre

Colour: Light grey

Recoating time: Around 6 hours depending on drying conditions

Solvent/Cleaning of tools: Water

Solid content: 40%

Density: 1.3 kg/litre at 25°C, varying slightly with colours

Washability: Not applicable

Drying time: About 2 hours at 20°C (touch dry)

SAFETY

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

ENVIRONMENTAL PROTECTION

This product is not classified as dangerous for the environment. This product should not be allowed to enter drains or water courses. Dispose of in accordance with regulations from local authorities.