

N O R D F Ä R G

TRÄ

Nordfärg Trä is an ultra high quality, waterborne, fast drying acrylic interior wood paint that offers easy application, has good levelling properties, is non-yellowing and almost odourless. Nordfärg Trä is tough, washable, has high dirt pick-up resistance and can be sprayed or applied with a brush or roller.

AREA OF USE

Interior: Primed wood and metal surfaces.

Substrates: Wood, metal, concrete, masonry, cement, rendered plaster, plasterboard and previously painted surfaces.

APPLICATION

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. Apply with brush, paint roller or spray. If necessary, dilute paint with max 5% of fresh water. Use only where application and drying can proceed above 5°C and relative humidity below 75%.

TECHNICAL INFORMATION

Sheen level: 5 (at 60°)

Coverage: 10m²/litre per coat, corresponding to about 35-50µ average dry film thickness

Colour: White and selected colours

Application: Brush, paint roller or spray

Recoating time: Between 4 and 8 hours depending on drying conditions

Solvent/Cleaning of tools: Water

Solid content: About 50% by weight or about 37% by volume (theoretical), varying slightly with colours

Density: 1.3 kg/litre at 25°C, varying slightly with colours

Washability: 10 000 laps

Drying time: About 2 hours at 20°C (touch dry)

SAFETY

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

ENVIRONMENTAL PROTECTION

This product is not classified as dangerous for the environment. This product should not be allowed to enter drains or water courses. Dispose of in accordance with regulations from local authorities.