

N O R D F Ä R G

VÄGG

Nordfärg Vägg is an extremely scratchproof, high quality waterborne paint for interior walls and ceilings. The end result is a velvety surface with no glossy appearance in raking light. Serving both as a primer and a top-coat, it ensures a smooth result without brush marks. As the painted surface is highly durable and washable it can withstand everyday wear and tear while maintaining it's elegance over a long time.

AREA OF USE

Interior: Walls, ceilings, roof tiles, wooden and metal surfaces.

Substrates: Concrete, cement, rendered plaster, plasterboard, lining paper, glass fibre, particleboard and previously painted surfaces.

APPLICATION

Surface must be clean, dry and free of dirt, scaling paint, loose wallpaper or any type of grease or wax. Wash previously painted surfaces with façade cleaner and rinse with water. Glossy surfaces must be sanded matt before painting. Moisture content of wood should not be more than 18% and do not apply in temperatures below +5°C or in humidity above 80%. Application to be carried out in accordance with BS 6250.

Apply primer undiluted in thin layers. At low temperatures and high humidity the drying time will be longer. Never paint on surfaces which are warm or in direct sunlight. Heat makes solvent evaporate much quicker which reduces the possibilities of achieving good adhesion.

TECHNICAL INFORMATION

Gloss level: 3-4 matt

Coverage: 7-9m²/litre

Colour: White and selected colours

Application: Brush, roller or spray (after dilution)

Recoating time: Minimum 4 hours

Shelf life: Max 2 years in dry, frost-free conditions

Cleaning of tools: Water

Resin: Styrene acrylic with ceramic microspheres

Washability: 15 000 laps

Drying time: 2-3 hours (touch dry)

SAFETY

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spraymist arising from the application of this preparation.

KEEP AWAY FROM CHILDREN

ENVIRONMENTAL PROTECTION

This product is not classified as dangerous for the environment. This product should not be allowed to enter drains or water courses. Dispose of in accordance with regulations from local authorities.